

WS 9220 ESD KLIMASTAR



Design

Material

Seat / Backrest	PUR integral foam / PUR integral foam
Five star base xx20 Ø655mm with dual castors (Ø 65mm)	diecast aluminium unloaded braked - loaded unbraked
Column xx20	safety gas spring, chrome plated
Backrest bow	high-precision steel bar, Ø20 x 2,0mm

Total height *	930 to 1215mm
----------------	---------------

Thickness of seat / backrest *	50mm / 50mm
--------------------------------	-------------

Weight *	16.60kg
----------	---------

Loading capacity	120kg
------------------	-------

Adjustabilities

Seat height (acc. DIN 68877) *	450 to 620mm
Seat tilt *	-8° to +1°
Seat lock	continuous
Backrest tilt *	-18° to +11°

Details

Backrest	
Width top / bottom *	325 / 400mm
Height *	450mm

Seat	
Width front / back *	470 / 415mm
Depth *	455mm

Characteristics

Conductivity	10 ⁴ Ohm to 10 ⁶ Ohm acc. EN 61340-5-1-1
--------------	--

*: production- or model-related differences are possible

Revision status	23.09.2019
-----------------	------------

We are constantly developing our products for you in design as well as in quality. Please contact us about your special requirements for work places and employees. We offer you individual solutions for special seat and standing work places.

WS 9220 ESD KLIMASTAR



*: The illustrated product may show accessories with surcharge.