

WS 1220 E GMP

Design

Material

Seat / Backrest	PUR integral foam / PUR integral foam
Five star base xx20 Ø655mm with dual castors (Ø 65mm)	diecast aluminium unloaded braked - loaded unbraked
Column xx20	safety gas spring, chrome plated, with column cover
Backrest steel bar	high-precision steel bar, Ø26 x 1,5mm

Total height *	715 to 1020mm
----------------	---------------

Thickness of seat / backrest *	35mm / 35mm
--------------------------------	-------------

Weight *	12.15kg
----------	---------

Loading capacity	120kg
------------------	-------

Adjustabilities

Seat height (acc. DIN 68877) *	460 to 610mm
Seat tilt *	-14,5° to +4,5°
Seat lock	continuous
Backrest tilt *	-7,5° to +23°

Details

Backrest	
Width *	420mm
Height *	300mm

Seat	
Width *	460mm
Depth *	435mm

Characteristics

Closed seat support cover made of plastic

*: production- or model-related differences are possible

Revision status	14.03.2016
-----------------	------------

We are constantly developing our products for you in design as well as in quality. Please contact us about your special requirements for work places and employees. We offer you individual solutions for special seat and standing work places.

WS 1220 E GMP



*: The illustrated product may show accessories with surcharge.